

CL21X series / Metallized polyester film capacitor(Stacked version)

■ Electrical Specification & Part Numbers Reference 规格型号参考 (mm)

Cap. (μF)	50VDC (30VAC)					Part Number
	W	H	T	P	d	
0.010	7.3	5.5	3.2	5.0	0.5	K4X1H103*****
0.012	7.3	5.5	3.2	5.0	0.5	K4X1H123*****
0.015	7.3	5.5	3.2	5.0	0.5	K4X1H153*****
0.018	7.3	5.5	3.2	5.0	0.5	K4X1H183*****
0.022	7.3	5.5	3.2	5.0	0.5	K4X1H223*****
0.027	7.3	5.5	3.2	5.0	0.5	K4X1H273*****
0.033	7.3	5.5	3.2	5.0	0.5	K4X1H333*****
0.039	7.3	5.5	3.2	5.0	0.5	K4X1H393*****
0.047	7.3	5.5	3.2	5.0	0.5	K4X1H473*****
0.056	7.3	5.5	3.2	5.0	0.5	K4X1H563*****
0.068	7.3	5.5	3.2	5.0	0.5	K4X1H683*****
0.082	7.3	5.5	3.2	5.0	0.5	K4X1H823*****
0.10	7.3	5.5	3.2	5.0	0.5	K4X1H104*****
0.12	7.3	5.5	3.2	5.0	0.5	K4X1H124*****
0.15	7.3	5.5	3.5	5.0	0.5	K4X1H154*****
0.18	7.3	5.5	4.0	5.0	0.5	K4X1H184*****
0.22	7.3	5.5	4.3	5.0	0.5	K4X1H224*****
0.27	7.3	7.0	4.3	5.0	0.5	K4X1H274*****
0.33	7.3	7.0	4.8	5.0	0.5	K4X1H334*****
0.39	7.3	7.0	5.0	5.0	0.5	K4X1H394*****
0.47	7.3	8.5	5.5	5.0	0.5	K4X1H474*****
0.56	7.3	8.5	5.8	5.0	0.5	K4X1H564*****
0.68	7.3	8.5	6.5	5.0	0.5	K4X1H684*****
0.82	7.3	9.5	6.5	5.0	0.5	K4X1H824*****
1.0	7.3	11.0	7.5	5.0	0.5	K4X1H105*****
1.2	10.0	9.5	5.5	7.5	0.5	K4X1H125*****
1.5	10.0	9.5	6.5	7.5	0.5	K4X1H155*****
1.8	10.0	11.0	6.5	7.5	0.5	K4X1H185*****
2.2	10.0	11.0	7.0	7.5	0.5	K4X1H225*****
2.7	10.0	13.5	7.0	7.5	0.5	K4X1H275*****
3.3	10.0	13.5	8.0	7.5	0.5	K4X1H335*****

Cap. (μF)	63VDC (40VAC)					Part Number
	W	H	T	P	d	
0.010	7.3	5.5	3.2	5.0	0.5	K4X1J103*****
0.012	7.3	5.5	3.2	5.0	0.5	K4X1J123*****
0.015	7.3	5.5	3.2	5.0	0.5	K4X1J153*****
0.018	7.3	5.5	3.2	5.0	0.5	K4X1J183*****
0.022	7.3	5.5	3.2	5.0	0.5	K4X1J223*****
0.027	7.3	5.5	3.2	5.0	0.5	K4X1J273*****
0.033	7.3	5.5	3.2	5.0	0.5	K4X1J333*****
0.039	7.3	5.5	3.2	5.0	0.5	K4X1J393*****
0.047	7.3	5.5	3.2	5.0	0.5	K4X1J473*****
0.056	7.3	5.5	3.2	5.0	0.5	K4X1J563*****
0.068	7.3	5.5	3.2	5.0	0.5	K4X1J683*****
0.082	7.3	5.5	3.2	5.0	0.5	K4X1J823*****
0.10	7.3	5.5	3.2	5.0	0.5	K4X1J104*****
0.12	7.3	5.5	3.2	5.0	0.5	K4X1J124*****
0.15	7.3	5.5	3.5	5.0	0.5	K4X1J154*****
0.18	7.3	5.5	4.0	5.0	0.5	K4X1J184*****
0.22	7.3	5.5	4.3	5.0	0.5	K4X1J224*****
0.27	7.3	7.0	4.3	5.0	0.5	K4X1J274*****
0.33	7.3	7.0	4.8	5.0	0.5	K4X1J334*****
0.39	7.3	7.0	5.0	5.0	0.5	K4X1J394*****
0.47	7.3	8.5	5.5	5.0	0.5	K4X1J474*****
0.56	7.3	8.5	5.8	5.0	0.5	K4X1J564*****
0.68	7.3	8.5	6.5	5.0	0.5	K4X1J684*****
0.82	7.3	9.5	6.5	5.0	0.5	K4X1J824*****
1.0	7.3	11.0	7.5	5.0	0.5	K4X1J105*****
1.2	10.0	9.5	5.5	7.5	0.5	K4X1J125*****
1.5	10.0	9.5	6.5	7.5	0.5	K4X1J155*****
1.8	10.0	11.0	6.5	7.5	0.5	K4X1J185*****
2.2	10.0	11.0	7.0	7.5	0.5	K4X1J225*****
2.7	10.0	13.5	7.0	7.5	0.5	K4X1J275*****
3.3	10.0	13.5	8.0	7.5	0.5	K4X1J335*****

备注 : 1. "*****" = Capacitance tolerance code, Pitch, Lead form and packaging code, Lead form, Lead length, Internal code.

"*****" 表示容量偏差, 引线脚距, 引线加工和包装代码, 引线加工脚距, 引线长度, 内部编码。

2. Customization for special specification and requirement is available.

CL23B series / Metallized polyester film capacitor(Stacked version)

■ Electrical Specification & Part Numbers Reference 规格型号参考 (mm)

Cap. (μ F)	100VDC (63VAC)					Part Number	Cap. (μ F)	250VDC (140VAC)					Part Number
	W	H	T	P	d			W	H	T	P	d	
0.010	7.3	5.5	3.2	5.0	0.5	K4X2A103*****	0.010	7.3	5.5	3.2	5.0	0.5	K4X2E103*****
0.012	7.3	5.5	3.2	5.0	0.5	K4X2A123*****	0.012	7.3	6.0	3.2	5.0	0.5	K4X2E123*****
0.015	7.3	5.5	3.2	5.0	0.5	K4X2A153*****	0.015	7.3	6.0	3.2	5.0	0.5	K4X2E153*****
0.018	7.3	5.5	3.2	5.0	0.5	K4X2A183*****	0.018	7.3	6.0	3.2	5.0	0.5	K4X2E183*****
0.022	7.3	5.5	3.2	5.0	0.5	K4X2A223*****	0.022	7.3	6.0	3.5	5.0	0.5	K4X2E223*****
0.027	7.3	5.5	3.2	5.0	0.5	K4X2A273*****	0.027	7.3	6.0	3.5	5.0	0.5	K4X2E273*****
0.033	7.3	5.5	3.2	5.0	0.5	K4X2A333*****	0.033	7.3	6.5	3.5	5.0	0.5	K4X2E333*****
0.039	7.3	5.5	3.2	5.0	0.5	K4X2A393*****	0.039	7.3	6.5	4.8	5.0	0.5	K4X2E393*****
0.047	7.3	5.5	3.2	5.0	0.5	K4X2A473*****	0.047	7.3	6.8	3.3	5.0	0.5	K4X2E473*****
0.056	7.3	5.5	3.2	5.0	0.5	K4X2A563*****	0.056	7.3	7.0	4.2	5.0	0.5	K4X2E563*****
0.068	7.3	5.5	3.2	5.0	0.5	K4X2A683*****	0.068	7.3	7.5	4.2	5.0	0.5	K4X2E683*****
0.082	7.3	5.5	3.2	5.0	0.5	K4X2A823*****	0.082	7.3	7.5	4.5	5.0	0.5	K4X2E823*****
0.10	7.3	5.5	3.2	5.0	0.5	K4X2A104*****	0.10	7.3	8.3	4.3	5.0	0.5	K4X2E104*****
0.12	7.3	5.5	3.2	5.0	0.5	K4X2A124*****	0.12	7.3	8.5	5.0	5.0	0.5	K4X2E124*****
0.15	7.3	5.5	3.5	5.0	0.5	K4X2A154*****	0.15	7.3	10.0	5.0	5.0	0.5	K4X2E154*****
0.18	7.3	5.5	4.0	5.0	0.5	K4X2A184*****	0.18	7.3	11.0	5.2	5.0	0.5	K4X2E184*****
0.22	7.3	5.5	4.3	5.0	0.5	K4X2A224*****	0.22	7.3	13.0	5.2	5.0	0.5	K4X2E224*****
0.27	7.3	7.0	4.3	5.0	0.5	K4X2A274*****							
0.33	7.3	7.0	4.8	5.0	0.5	K4X2A334*****							
0.39	7.3	7.0	5.0	5.0	0.5	K4X2A394*****							
0.47	7.3	8.5	5.5	5.0	0.5	K4X2A474*****							
0.56	7.3	8.5	5.8	5.0	0.5	K4X2A564*****							
0.68	7.3	8.5	6.5	5.0	0.5	K4X2A684*****							
0.82	7.3	9.5	6.5	5.0	0.5	K4X2A824*****							
1.0	7.3	11.0	7.5	5.0	0.5	K4X2A105*****							

备注：1. “*****” = Capacitance tolerance code, Pitch, Lead form and packaging code, Lead form, Lead length, Internal code.
 “*****” 表示容量偏差，引线脚距，引线加工和包装代码，引线加工脚距，引线长度，内部编码。

2. Customization for special specification and requirement is available.